

# PETROMERICA

## Full Synthetic Multi-Vehicle ATF

**PETROMERICA FULL SYNTHETIC MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID** provides extreme transmission protection including additional oxidation control, excellent low temperature and superior shear stability performance in modern passenger car, flex-fuel vehicle, hybrid, truck, and sport utility vehicle transmissions. It is suitable for use in automatic transmissions calling for DEXRON®-VI, DEXRON® II/III/III-E/III-H, Ford MERCON®LV, Allison C-3 & C-4, CAT TO-2, Chrysler ATF+3 +4, Honda Z-1, DW-1, Hyundai/Kia SP-II/III/IV, JASO 1A, 2A, Nissan Matic Fluids, Toyota T-III, T-IV, WS and many other American, Asian and European OEM's performance standards including Mercedes Benz NAG 1, MAN 339A, Mazda, Mitsubishi, Subaru, Porsche, Voith 55.6335, VW, ZF TE-ML 21L, ZF 8 & 9 speed and BMW 4- and 5-speed automatic transmission specifications.

### BENEFITS AND APPLICATIONS

- Full synthetic maximum corrosion, wear, and rust protection
- Outstanding low temperature flow properties
- Enhanced friction additives and oxidation stability for longer fluid life
- Smooth shifting and reduce shudder performance
- High compatibility - suitable for use in most applications

### Typical Characteristics - MV ATF - V221129

GRADE	Test Method	MV ATF
Color	Visual	Red
Viscosity @ 100°C, cSt	ASTM D445	7.1
Viscosity @ 40°C, cSt	ASTM D445	32.0
Viscosity Index	ASTM D2270	150
Pour Point, °C/°F	ASTM D97	-48 / -54.4
Flash Point, COC °C/°F	ASTM D92	208 / 406.4
API Gravity	ASTM D287	32.8
Brookfield Vis.cP @ -40°C	ASTM D2983	16200

Typical test data are average values only.  
Minor variations, which do not affect performance, may occur.

**Suitable for:**  
DEXRON®-VI,  
DEXRON®-II/III/III-E/III-H  
MERCON®LV,  
JASO 1A, 2A, Toyota,  
Mercedes Benz®  
Nissan®Matic Fluids  
Honda® Z1



Manufactured by US Global Petroleum, Franklin Park, IL 60131 - 773-376-9660

HANDLING AND SAFETY INFORMATION - Refer to USGLOBAL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

[www.usglobalpetroleum.com](http://www.usglobalpetroleum.com)

[www.petromericaoil.com](http://www.petromericaoil.com)